

Datum: 08.12.2025

Davčna št.: SI35517140
Telefon: 041 596 992
E-mail: info@piara.net
WWW: www.piara.net

ASUS PRIME B650M-A II-CSM, DDR5, SATA3, USB3.2Gen2, DP, 2.5GbE, AM5 mATX

Kategorija: [Osnovne plošče](#)
Šifra:



Redna cena z DDV: **132,37 €**

Na zalogi

(slika je simbolična)

PODNOŽJE: AMD AM5

ZA PROCESORJE: AMD RYZEN 7000 Series

FORMAT: ATX format 24.4 cm x 24.4 cm

VEZNI ČIP: AMD B650

POMNILNIK:

4 x DDR5 DIMM ECC and Non-ECC, Un-buffered Memory

7600(OC)/7200(OC)/7000(OC)/6800(OC)/6600(OC)/6400(OC)/6200(OC)/6000(OC)/5800(OC)/5600(OC)/5400(OC)/5200/5000/4800MHz
(odvisno od procesorja) do skupno 192GB kapacitete, dual channel in EXtended Profiles for Overclocking, OptiMem II podpora

GRAFIKA: DA - preko APU

RAID: DA (0,1,10)

RAZŠIRITVENE REŽE:

1 x PCI Express 3.0/4.0 x16

1 x PCI Express 3.0/4.0 x8/x4

2 x PCI Express 3.0/4.0 x1

MREŽNA KARTICA: Realtek 2.5GbE LAN chip (10/100/1000Mbit/2.5Gbit)

ZVOČNA KARTICA: Realtek Audio codec High Definition Audio (2/4/5.1/7.1-channel)

NOTRANJI PRIKLJUČKI:

Fan and Cooling related

1 x 4-pin CPU Fan header

1 x 4-pin CPU OPT Fan header

3 x 4-pin Chassis Fan headers

Power related

1 x 24-pin Main Power connector

1 x 8-pin +12V Power connector

Storage related

2 x M.2 slots (Key M)

4 x SATA 6Gb/s ports

USB

1 x USB 3.2 Gen 1 connector (supports USB Type-C®)

1 x USB 3.2 Gen 1 header supports 2 additional USB 3.2 Gen 1 ports

2 x USB 2.0 headers support 4 additional USB 2.0 ports

Miscellaneous

3 x Addressable Gen 2 headers

1 x Aura RGB header

1 x Clear CMOS header

1 x COM Port header

1 x Front Panel Audio header (AAFP)

1 x S/PDIF Out header

1 x Speaker header

1 x SPI TPM header (14-1pin)

1 x 10-1 pin System Panel header

ZUNANJI PRIKLJUČKI:

2 x USB 3.2 Gen 2 ports (2 x Type-A)

2 x USB 3.2 Gen 1 ports (2 x Type-A)

4 x USB 2.0 ports (4 x Type-A)

1 x DisplayPort

1 x VG

Specifikacije

Procesor	AM5
Ram	DDR5

A port
1 x HDMI® port
1 x Realtek 2.5Gb Ethernet port
3 x Audio jacks
1 x BIOS FlashBack™ button
1 x PS/2 Keyboard/Mouse combo port
DODATNO:
Fan and Cooling related
1 x 4-pin CPU Fan header
1 x 4-pin CPU OPT Fan header
3 x 4-pin Chassis Fan headers
Power related
1 x 24-pin Main Power connector
1 x 8-pin +12V Power connector
Storage related
2 x M.2 slots (Key M)
4 x SATA 6Gb/s ports
USB
1 x USB 3.2 Gen 1 connector (supports USB Type-C®)
1 x USB 3.2 Gen 1 header supports 2 additional USB 3.2 Gen 1 ports
2 x USB 2.0 headers support 4 additional USB 2.0 ports
Miscellaneous
3 x Addressable Gen 2 headers
1 x Aura RGB header
1 x Clear CMOS header
1 x COM Port header
1 x Front Panel Audio header (AAFP)
1 x S/PDIF Out header
1 x Speaker header
1 x SPI TPM header (14-1pin)
1 x 10-1 pin System Panel header
Special Features
ASUS 5X PROTECTION III
- DIGI+ VRM
- LANGuard
- Overvoltage Protection
- Safeslot Core+
- Stainless-Steel Back I/O
ASUS Q-Design
- Q-DIMM
- Q-LED Core
- Q-Slot
ASUS Thermal Solution
- VRM heatsink design
ASUS EZ DIY
- BIOS FlashBack™ button
- BIOS FlashBack™ LED
Aura Sync
- Aura RGB header
- Addressable Gen 2 headers
Software Features
ASUS Exclusive Software
Armoury Crate
- Aura Creator
- Aura Sync
- Fan Xpert 2+
- Power Saving
AI Suite 3
- TurboV EVO
- DIGI+ VRM
- PC Cleaner
ASUS CPU-Z
Norton Anti-virus software (Free Trial version)
WinRAR
UEFI BIOS
ASUS EZ DIY
- ASUS CrashFree BIOS 3
- ASUS EZ Flash 3
- ASUS UEFI BIOS EZ Mode

Spletna stran proizvajalca: <https://www.asus.com/motherboards-components/motherboards/csm/prime-b650m-a-ii-csm/>
