

Datum: 08.12.2025

Davčna št.: SI35517140
Telefon: 041 596 992
E-mail: info@piara.net
WWW: www.piara.net

**GIGABYTE B550 AORUS ELITE V2, DDR4, SATA3,
USB3.2Gen2, DP, 2.5GbE, AM4 ATX**



Kategorija: [Osnovne plošče](#)
Šifra:

Redna cena z DDV: **125,66 €**

Na zalogi

(slika je simbolična)

PODNOŽJE: AMD AM4

ZA PROCESORJE: AMD RYZEN

FORMAT: ATX format 30.5 cm x 24.4 cm

VEZNI ČIP: AMD B550

POMNILNIK:

4 x DDR4 DIMM ECC/non-ECC do **4733(O.C.) / 4600(O.C.) / 4400(O.C.) / 4266(O.C.) / 4133(O.C.) / 4000(O.C.) / 3866(O.C.) / 3733(O.C.) / 3600(O.C.) / 3466(O.C.) / 3400(O.C.) / 3200 / 2933 / 2667 / 2400 / 2133 MHz**

(odvisno od procesorja) do skupno 128GB kapacitete, dual channel in **Extreme Memory Profile (XMP)** podpora

GRAFIKA: DA - preko APU

RAID: DA (0,1,10)

RAZŠIRITVENE REŽE:

1 x PCI Express x16 slot (PCIEX16), integrated in the CPU:

- AMD Ryzen™ 5000 Series and Ryzen™ 3000 Series Processors support PCIe 4.0 x16 mode

- AMD Ryzen™ Ryzen™ 5000 G-Series and Ryzen™ 4000 G-Series Processors support PCIe 3.0 x16 mode

* For optimum performance, if only one PCI Express graphics card is to be installed, be sure to install it in the PCIEX16 slot.

1 x PCI Express x16 slot (PCIEX2), integrated in the Chipset:

- Supporting PCIe 3.0 x2 mode

1 x PCI Express x16 slot (PCIEX1_2), integrated in the Chipset:

- Supporting PCIe 3.0 x1 mode

1 x PCI Express x1 slot (PCIEX1_1), integrated in the Chipset:

- Supporting PCIe 3.0 x1 mode

MREŽNA KARTICA: Realtek 2.5GbE LAN chip (10/100/1000Mbit/2.5Gbit)

ZVOČNA KARTICA: Realtek ALC1200-VB codec High Definition Audio (2/4/5.1/7.1-channel)

NOTRANJI PRIKLJUČKI:

1 x 24-pin ATX main power connector

1 x 8-pin ATX 12V power connector

2 x M.2 Socket 3 connectors

4 x SATA 6Gb/s connectors

1 x CPU fan header

1 x water cooling CPU fan header

3 x system fan headers

1 x CPU cooler LED strip/RGB LED strip h

Specifikacije

Procesor AM4

Ram DDR4

header
2 x addressable LED strip headers
2 x RGB LED strip headers
1 x front panel header
1 x front panel audio header
1 x USB Type-C™ port, with USB 3.2 Gen 1 support
1 x USB 3.2 Gen 1 header
2 x USB 2.0/1.1 headers
1 x Trusted Platform Module (TPM) header (2x6 pin, for the GC-TPM2.0_S module only)
1 x Clear CMOS jumper

ZUNANJI PRIKLJUČKI:

1 x DisplayPort
1 x HDMI port
2 x USB 3.2 Gen 2 Type-A ports (red)
3 x USB 3.2 Gen 1 ports
2 x USB 2.0/1.1 ports
1 x Q-Flash Plus button
1 x RJ-45 port
1 x optical S/PDIF Out connector
5 x audio jacks

DODATNO:

iTE® I/O Controller Chip
H/W Monitoring
Voltage detection
Temperature detection
Fan speed detection
Water cooling flow rate detection
Overheating warning
Fan fail warning
Fan speed control
BIOS
1 x 256 Mbit flash
Use of licensed AMI UEFI BIOS
PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0
Unique Features
Support for APP Center
@BIOS
EasyTune
Fast Boot
Game Boost
ON/OFF Charge
RGB Fusion
Smart Backup
System Information Viewer
Support for Q-Flash Plus
Support for Q-Flash
Support for Xpress Install
Bundled Software
Norton® Internet Security (OEM version)
Realtek® 8125 Gaming LAN Bandwidth Control Utility

Spletna stran proizvajalca: <https://www.gigabyte.com/Motherboard/B550-AORUS-ELITE-V2-rev-15#kf>
