

Datum: 08.12.2025

Davčna št.: SI35517140
Telefon: 041 596 992
E-mail: info@piara.net
WWW: www.piara.net

**GIGABYTE B650 GAMING X AX V2, DDR5, SATA3,
USB3.2Gen2x2, DP, 2.5GbE, WiFi 6E, AM5 ATX**

Kategorija: [Osnovne plošče](#)
Šifra:

Redna cena z DDV: **165,92 €**

Na zalogi



(slika je simbolična)

PODNOŽJE: AMD AM5

ZA PROCESORJE: AMD Ryzen 7000/8000/9000 Series

FORMAT: ATX format 30.5 cm x 24.4 cm

VEZNI ČIP: AMD B650

POMNILNIK:

4 x DDR5 DIMM non-ECC 8000(OC)/ 7800(OC)/ 7600(OC)/
7200(OC)/ 7000(OC)/ 6800(OC)/ 6600(OC)/ 6400(OC)/ 6200(OC)/
6000(OC)/ 5600(OC)/ 5200/ 4800/ 4400MHz (odvisno od
procesorja) do skupno 256GB kapacitete, dual channel in
EXtended Profiles for Overclocking, Extreme Memory Profile (XMP)
podpora

GRAFIKA: DA - preko APU

RAID: DA (0,1,10) support for SATA/NVME storage devices

RAZŠIRITVENE REŽE:

1 x PCI Express x16 slot (PCIEX16)

MREŽNA KARTICA: Realtek 2.5GbE LAN chip (2.5 Gbps/1
Gbps/100 Mbps)

Realtek Wi-Fi 6E RTL8852CE (PCB rev. 1.0)

WIFI a, b, g, n, ac, ax, supporting 2.4/5/6 GHz + BLUETOOTH 5.3 +
11ax 160MHz wireless standard

AMD Wi-Fi 6E RZ616 (MT7922A22M) (PCB rev. 1.1)

WIFI a, b, g, n, ac, ax, supporting 2.4/5/6 GHz + BLUETOOTH 5.2 +
Support for 11ax 160MHz

Intel Wi-Fi 6E AX210 (PCB rev. 1.2)

WIFI a, b, g, n, ac, ax, supporting 2.4/5/6 GHz + BLUETOOTH 5.3 +
Support for 11ax 160MHz

ZVOČNA KARTICA: Realtek Audio CODEC High Definition Audio
(2/4/5.1/7.1-channel)

NOTRANJI PRIKLJUČKI:

1 x 24-pin ATX main power connector

1 x 8-pin ATX 12V power connector

1 x 4-pin ATX 12V power connector

1 x CPU fan header

1 x CPU fan/water cooling pump header

2 x system fan headers

1 x system fan/water cooling pump header

2 x addressable LED strip headers

2 x RGB LED strip headers

1 x CPU cooler LED strip/RGB LED strip header

3 x M.2 Socket 3 connectors

4 x SATA 6Gb/s connectors

1 x front panel he

Specifikacije

Processor AM5

Ram DDR5

ader

1 x front panel audio header

1 x USB Type-C® header, with USB 3.2 Gen 2x2 support

1 x USB 3.2 Gen 1 header

2 x USB 2.0/1.1 headers

1 x Trusted Platform Module header (For the GC-TPM2.0 SPI/GC-TPM2.0 SPI 2.0/GC-TPM2.0 SPI V2 module only)

1 x serial port header

1 x reset button

1 x reset jumper

1 x Clear CMOS jumper

ZUNANJI PRIKLJUČKI:

2 x SMA antenna connectors (2T2R)

1 x Q-Flash Plus button

1 x DisplayPort

1 x HDMI port

1 x USB Type-C® port, with USB 3.2 Gen 2 support

1 x USB 3.2 Gen 2 Type-A port (red)

3 x USB 3.2 Gen 1 ports

3 x USB 2.0/1.1 ports

1 x RJ-45 port

3 x audio jacks

DODATNO:

iTE® I/O Controller Chip

H/W Monitoring

Voltage detection

Temperature detection

Fan speed detection

Water cooling flow rate detection

Fan fail warning

Fan speed control

BIOS

1 x 256 Mbit flash

Use of licensed AMI UEFI BIOS

PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0

Unique Features

Support for GIGABYTE Control Center (GCC)

Support for Q-Flash

Support for Q-Flash Plus

Bundled Software

Norton® Internet Security (OEM version)

LAN bandwidth management software

Uradna stran proizvajalca: <https://www.gigabyte.com/Motherboard/B650-GAMING-X-AX-V2-rev-1x>
