

Datum: 08.12.2025

Piara.net - Računalniški servis in trgovina  
Cesta v Mestni log 55, Ljubljana

Davčna št.: SI35517140  
Telefon: 041 596 992  
E-mail: [info@piara.net](mailto:info@piara.net)  
WWW: [www.piara.net](http://www.piara.net)

### MikroTik hAP ac lite usmerjevalnik (RB952Ui-5ac2nD)

Kategorija: [Mrežna oprema](#)  
Šifra:

Redna cena z DDV: **60,88 €**

**Na zalogi**



(slika je simbolična)

HAP ac lite je dvojna sočasna dostopna točka, ki omogoča pokritje Wifi hkrati za frekvence 2,4GHz in 5GHz.

Enota je opremljena z 650MHz CPU, 64MB RAM-a, petimi 10 / 100Mbps Ethernet vrati (PoE izhod na vrata # 5), dvo verižnim brezžičnim 802.11b / g / n 2.4GHz brezžičnim omrežjem, eno verigo 802.11ac 5GHz brezžičnim omrežjem, USB vhodom za 3G / 4G modem in licenco RouterOS L4.

Mikrotik ima na voljo dve različici - RB952Ui-5ac2nD (International) in RB952Ui-5ac2nD-US (ZDA). RB952Ui-5ac2nD-US (ZDA) je tovarniško zaklenjen za frekvence 2412-2462MHz, 5150-5250MHz in 5725-5850MHz. Te ključavnice ni mogoče odstraniti. RB952Ui-5ac2nD (International) podpira območje 2412-2484MHz in 5150MHz - 5875MHz.

## Specifications

| Details                    |                 |
|----------------------------|-----------------|
| Product code               | RB952Ui-5ac2nD  |
| Architecture               | MIPSBE          |
| CPU                        | QCA9531         |
| CPU core count             | 1               |
| CPU nominal frequency      | 650 MHz         |
| Dimensions                 | 113 x 89 x 28mm |
| License level              | 4               |
| Operating System           | RouterOS        |
| Size of RAM                | 64 MB           |
| Storage size               | 16 MB           |
| Storage type               | FLASH           |
| Tested ambient temperature | -30°C to 70°C   |
| Suggested price            | \$49.95         |

## Powering

| Details                                |                     |
|----------------------------------------|---------------------|
| PoE in                                 | Passive PoE         |
| PoE in input Voltage                   | 12-30 V             |
| PoE out                                | Passive PoE         |
| PoE-out ports                          | Ether5              |
| Number of DC inputs                    | 2 (DC jack, PoE-IN) |
| DC jack input Voltage                  | 10-30 V             |
| Max out per port output (input < 30 V) | 500 mA              |
| Max total out (A)                      | 500 mA              |
| Max power consumption                  | 8 W                 |

## Wireless

| Details                      |             |
|------------------------------|-------------|
| AC speed                     | AC750       |
| Antenna gain dBi for 2.4 GHz | 2           |
| Wireless 2.4 GHz standards   | 802.11b/g/n |
| Wi-Fi generation             | 5           |
| Wirele                       |             |

## Specifikacije

Vrsta naprave   Usmerjevalnik

|                                   |              |
|-----------------------------------|--------------|
| ss 2.4 GHz Max data rate          | 300 Mbit/s   |
| Wireless 5 GHz Max data rate      | 433 Mbit/s   |
| Wireless 2.4 GHz number of chains | 2            |
| Wireless 2.4 GHz chip model       | QCA9531      |
| Wireless 5 GHz number of chains   | 1            |
| Wireless 5 GHz standards          | 802.11a/n/ac |
| Antenna gain dBi for 5 GHz        | 2            |
| Wireless 5 GHz chip model         | QCA9887      |

## Ethernet

| Details               |   |
|-----------------------|---|
| 10/100 Ethernet ports | 5 |

## Peripherals

| Details             |   |
|---------------------|---|
| Number of USB ports | 1 |

| Details             |            |
|---------------------|------------|
| USB Power Reset     | Yes        |
| USB slot type       | USB type A |
| Max USB current (A) | 1          |

Več na: [uradni strani](#)