

Datum: 08.12.2025

Osnovna plošča LGA1851 GigaByte DS3H WIFI6E ATX HDMI DP

Kategorija: [Osnovne plošče](#)
Šifra:

Redna cena z DDV: **224,29 €**
Cena s popustom z DDV: **188,11 €**

Na zalogi



(slika je simbolična)

PODNOŽJE: INTEL LGA 1851

ZA PROCESORJE: Intel Core Ultra Processors

FORMAT: ATX format 30.5 cm x 24.4 cm

VEZNI ČIP: INTEL B860

POMNILNIK:

4 x DDR5 DIMM ECC/non-ECC 9066(O.C)/8800(O.C)/8600(O.C) /
8400(O.C)/8266(O.C) / 8200(O.C) / 8000(O.C) / 7950(O.C) / 7900(O.C) /
7800(O.C) / 7600(O.C.) / 7400(O.C.) / 7200(O.C.) / 7000(O.C.) /
6800(O.C.) / 6600(O.C.) / 6400 / 5600MHz) do skupno 256GB kapacitete,
dual channel in XMP podpora, ECC/non-ECC podpora

GRAFIKA: DA - preko CPU

RAID: RAID 0, RAID 1, RAID 5, and RAID 10

RAZŠIRITVENE REŽE:

1 x PCI Express 5.0 x16

4 x PCI Express 4.0 x1

MREŽNA KARTICA: Realtek 2.5GbE LAN chip + Intel Wi-Fi 6E

AX211 WIFI a, b, g, n, ac, ax + BLUETOOTH 5.3

ZVOČNA KARTICA: Realtek codec High Definition Audio (2/4/5.1/7.1-
channel)

NOTRANJI PRIKLJUČKI:

1 x 24-pin ATX main power connector

1 x 8-pin ATX 12V power connector

1 x CPU fan header

1 x CPU fan/water cooling pump header

2 x system fan headers

2 x system fan/water cooling pump headers

3 x addressable RGB Gen2 LED strip headers

1 x RGB LED strip header

2 x M.2 Socket 3 connectors

4 x SATA 6Gb/s connectors

1 x front panel header

1 x front panel audio header

1 x S/PDIF Out header

1 x USB Type-C header, with USB 3.2 Gen 1 support

1 x USB 3.2 Gen 1 header

2 x USB 2.0/1.1 headers

1 x Trusted Platform Module header (For the GC-TPM2.0 SPI/GC-TPM2.0

SPI 2.0/GC-TPM2.0 SPI V2 module only)

1 x serial port header

1 x Q-Flash Plus button

1 x reset jumper

1 x Clear CMOS jumper

ZUNANJI PRIKLJUČKI:

1 x PS/2 keyboard/mouse port

1 x HDMI port

1 x Di

Specifikacije

Ram DDR5

splayPort

1 x USB Type-C port, with USB 3.2 Gen 2x2 support

1 x USB 3.2 Gen 2 Type-A port (red)

4 x USB 2.0/1.1 ports

1 x RJ-45 port

2 x antenna connectors (2T2R)

3 x audio jacks

DODATNO:

iTE I/O Controller Chip

H/W Monitoring

Voltage detection

Temperature detection

Fan speed detection

Water cooling flow rate detection

Fan fail warning

Fan speed control

BIOS

1 x 256 Mbit flash

Use of licensed AMI UEFI BIOS

PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0

Unique Features

Support for GIGABYTE Control Center (GCC)

Support for Q-Flash

Support for Q-Flash Plus

Support for Smart Backup

Bundled Software

Norton Internet Security (OEM version)

LAN bandwidth management software

Spletna stran proizvajalca: <https://www.gigabyte.com/Motherboard/B860-DS3H-WIFI6E/sp#sp>
