

Datum: 08.12.2025

Piara.net - Računalniški servis in trgovina
Cesta v Mestni log 55, Ljubljana

Davčna št.: SI35517140
Telefon: 041 596 992
E-mail: info@piara.net
WWW: www.piara.net

[TP-LINK 24-Port 10/100Mbps Rackmount stikalo](#)

Kategorija: [Mrežna oprema](#)

Šifra:



Redna cena z DDV: **59,19 €**

Na zalogi

(slika je simbolična)

HARDWARE FEATURES	
Standards and Protocols	IEEE 802.3i, IEEE 802.3u, IEEE 802.3x
Interface	24 10/100Mbps RJ45 Ports (Auto Negotiation/Auto MDI/MDIX)
Network Media	10BASE-T: UTP category 3, 4, 5 cable (maximum 100m) 100BASE-TX: UTP category 5, 5e or above cable (maximum 100m)
Fan Quantity	Fanless
Power Supply	100-240VAC, 50/60Hz
Power Consumption	Maximum: 3.53W (220V/50Hz)
Dimensions (W x D x H)	17.3*7.1*1.7 in. (440*180*44 mm)
Mounting	Rack Mountable
Max Power Consumption	3.19W(220V/50Hz)
Max Heat Dissipation	10.88BTU/h

PERFORMANCE	
Switching Capacity	4.8Gbps
Packet Forwarding Rate	3.57Mpps
MAC Address Table	8K
Buffer Memory	2Mb
Green Technology	Innovative energy-efficient technology saves power up to 75%
Transfer Method	Store-and-Forward

OTHERS	
Certification	FCC, CE, RoHS
Package Contents	24-Port 10/100Mbps Rackmount Switch Power Cord Installation Guide Rackmount Kit Rubber Feet
System Requirements	Microsoft® Windows® 8, 7, Vista™, XP or MAC® OS, NetWare®, UNIX® or Linux.
Environment	Operating Temperature: 0°C~40°C (32°F~104°F); Storage Temperature: -40°C~70°C (-40°F~158°F); Operating Humidity: 10%~90% non-condensing; Storage Humidity: 5%~90% non-condensing

Več na: <https://www.tp-link.com/se/service-provider/unmanaged-switch/tl-sf1024/#overview>

Specifikacije

Vrsta naprave Stikalo