

Datum: 08.12.2025

Davčna št.: SI35517140
Telefon: 041 596 992
E-mail: info@piara.net
WWW: www.piara.net

TP-LINK 8-Port 10/100Mbps namizno stikalo s 4 porti PoE

Kategorija: [Mrežna oprema](#)
Šifra:

Redna cena z DDV: **42,16 €**

Na zalogi



(slika je simbolična)

HARDWARE FEATURES	
Interface	8 10/100Mbps RJ45 Ports AUTO Negotiation/AUTO MDI/MDIX
Network Media	10BASE-T: UTP category 3, 4, 5 cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m) 100BASE-TX: UTP category 5, 5e cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m)
Fan Quantity	Fanless
Power Consumption	Maximum (PoE on): 60.2W (220V/50Hz) Maximum (PoE off): 3.2W (220V/50Hz)
External Power Supply	External Power Adapter(Output: 48VDC / 1.25A)
PoE Ports (RJ45)	Standard: 802.3 af compliant PoE Ports: Port1- Port4 Power Supply: 57W
Backbound Bandwidth	1.6Gbps
Mac Address Table	2K
Dimensions (W x D x H)	6.7*3.9*1.1 in. (171*98*27 mm)
Max Power Consumption	2.66(220/50Hz. no PD connected) 65.92(220/50Hz. with 57W PD connected)
Max Heat Dissipation	9.08BTU/h(no PD connected) 224.92BTU/h(with 57W PD connected)
SOFTWARE FEATURES	
Transmission Method	Store-And-Forward
Advanced Functions	Compatible With IEEE 802.3af Compliant PDs Priority Function Mac Address Auto-Learning And Auto-Aging IEEE802.3x Flow Control For Full-Duplex Mode And Backpressure For Half-Duplex Mode
OTHERS	
Certification	FCC, CE, RoHS
Package Contents	TL-SF1008P, Power Adapter, User Guide
Consumption	2.3 watts (max. no PD connected) 59.3 watts (max. with 57w PD connected)
Environment	Operating Temperature: 0°C~40°C (32°F~104°F) Storage Temperature: -40°C~70°C (-40°F~158°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing

Specifikacije

Vrsta naprave Stikalo

