

Datum: 08.12.2025

Davčna št.: SI35517140
Telefon: 041 596 992
E-mail: info@piara.net
WWW: www.piara.net



TP-LINK usmerjevalnik Archer AX73 AX5400 Dual Band Gigabit usmerjevalnik Wi-Fi 6

Kategorija: [Mrežna oprema](#)
Šifra:

Redna cena z DDV: **137,76 €**

Na zalogi

(slika je simbolična)

Gigabitni Wi-Fi 6 hitrosti naslednje generacije - 4804 Mbps pri 5 GHz in 574 Mbps v pasu 2,4 GHz zagotavlja gladko pretakanje in hitrejše prenose
Poveži več naprav - tehnologija OFDMA poveča zmogljivost za 4-krat, da omogoči hkratni prenos na več naprav
Ultra-nizka zakasnitev - omogoča bolj odzivno igranje iger in video klepetanje
Razširjena pokritost Wi-Fi - štiri zunanje antene z visokim izkoristkom in tehnologija Beamforming skupaj razširijo močan in zanesljiv Wi-Fi po vsem vašem domu
TP-Link HomeShield - Izboljšana varnost ščiti pred najnovejšimi kibernetnimi grožnjami
OneMesh - Brez zamenjave obstoječih naprav ali nakupa popolnoma novega ekosistema WiFi vam OneMesh pomaga ustvariti bolj prilagodljivo omrežje, ki pokriva celoten dom z izdelki TP-Link OneMesh

Standards Wi-Fi 6

IEEE 802.11ax/ac/n/a 5 GHz

IEEE 802.11ax/n/b/g 2.4 GHz

WiFi Speeds AX5400

5 GHz: 4804 Mbps (802.11ax, HE160)

2.4 GHz: 574 Mbps (802.11ax)

WiFi Range 3 Bedroom Houses

6x Fixed High-Performance Antennas

Multiple antennas form a signal-boosting array to cover more directions and large areas

Beamforming

Concentrates wireless signal strength towards clients to expand WiFi range

High-Power FEM

Improves transmission power to strengthen signal coverage

4T4R

Multiple streams in the same band strengthen the fault tolerance in transmission

WiFi Capacity High

Dual-Band

Allocate devices to different bands for optimal performance

4x4 MU-MIMO

Simultaneously communicates with multiple MU-MIMO clients

OFDMA

Simultaneously communicates with mul

Specifikacije

Vrsta naprave Usmerjevalnik

Supports up to 16 Wi-Fi 6 clients

Airtime Fairness

Improves network efficiency by limiting excessive occupation

DFS

Access an extra band to reduce congestion

6 Streams

Connect your devices to more bandwidth

Working Modes Router Mode

Access Point Mode

HARDWARE

Processor 1.5 GHz Triple-Core CPU

Ethernet Ports 1× Gigabit WAN Port

4× Gigabit LAN Ports

Static Link Aggregation (LAG) available with 2× LAN ports

USB Support 1× USB 3.0 Port

Supported Partition Formats:

NTFS, exFAT, HFS+, FAT32

Supported Functions:

Apple Time Machine

FTP Server

Media Server

Samba Server

Buttons Wi-Fi On/Off Button

Power On/Off Button

LED On/Off Button

WPS Button

Reset Button

Power 12 V □ 2.5 A

SECURITY

WiFi Encryption WPA

WPA2

WPA3

WPA/WPA2-Enterprise (802.1x)

Network Security SPI Firewall

Access Control

IP & MAC Binding

Application Layer Gateway

HomeShield Security

Real-Time IoT Protection

Malicious Site Blocker

Intrusion Prevention System

DDoS Attack Prevention

Home Network Scanner

Guest Network 1× 5 GHz Guest Network

1× 2.4 GHz Guest Network

VPN Server OpenVPN

PPTP

SOFTWARE

Protocols IPv4

IPv6

Service Kits HomeShield

[Learn More>](#)

OneMesh™ OneMesh™ Supported

Without replacing your existing devices or buying a whole new WiFi ecosystem, OneMesh™ helps you create a more flexible network that covers your entire home with TP-Link OneMesh™ products.

[Learn More>](#)

[All OneMesh Products>](#)

Parental Controls HomeShield Parental Controls

Custom Profiles

Professional Content Filter Library

Family Time

Bedtime

Off Time

Time Rewards

Family Online Time Ranking

Pause the Internet

Weekly and Mon

thly Reports
WAN Types Dynamic IP
Static IP
PPPoE
PPTP
L2TP
Quality of Service QoS by Device
Cloud Service Auto Firmware Upgrade
TP-Link ID
DDNS
NAT Forwarding Port Forwarding
Port Triggering
DMZ
UPnP
Virtual Server
IPTV IGMP Proxy
IGMP Snooping
Bridge
Tag VLAN
DHCP Address Reservation
DHCP Client List
Server
DDNS TP-Link
NO-IP
DynDNS
Management Tether App
Webpage
PHYSICAL
Dimensions (WxDxH) 10.7 × 5.8 × 1.9 in
(272.5 × 147.2 × 49.2 mm)
Package Contents Wi-Fi Router Archer AX73
Power Adapter
RJ45 Ethernet Cable
Quick Installation Guide
OTHER
System Requirements Internet Explorer 11+, Firefox 12.0+, Chrome 20.0+, Safari 4.0+, or other JavaScript-enabled browser
Cable or DSL Modem (if needed)
Subscription with an internet service provider (for internet access)
Certifications FCC, CE, RoHS
Environment Operating Temperature: 0°C~40°C (32°F ~104°F)
Storage Temperature: -40°C~70°C (-40°F ~158°F)
Operating Humidity: 10%~90% non-condensing
Storage Humidity: 5%~90% non-condensing
TEST DATA
WiFi Transmission Power CE:
<20dBm{2.4GHz}
<23dBm{5.15GHz~5.35GHz}
<30dBm{5.47GHz~5.725GHz}
FCC:
<24dBm{5.25GHz~5.35GHz&5.47GHz~5.725GHz }
<30dBm{2.4GHz &5.15GHz~5.25GHz&5.725GHz~5.825GHz }
WiFi Reception Sensitivity 2.4GHz:
11ac VHT20 MCS0:-94.5dBm
11ac VHT20 MCS8:-72.5dBm
11ac VHT40 MCS0:-92.5dBm
11ac VHT40 MCS9:-69.5dBm
11ax HE20 MCS0:-95dBm
11ax HE20 MCS11:-64.5dBm
11ax HE40 MCS0:-92.5dBm
11ax HE40 MCS11:-62dBm
5GHz:
11ac VHT20 MCS0:-97dBm
11ac VHT20 MCS8:-74dBm
11ac VHT40 MCS0:-95dBm
11ac VHT40 MCS9:-70dBm
11ac VHT80 MCS0:-91.5dBm
11ac VHT80 MCS9:-66dBm
11ac VHT

160 MCS0:-86dBm
11ac VHT160 MCS9:-61dBm
11ax HE20 MCS0:-95dBm
11ax HE20 MCS11:-64dBm
11ax HE40 MCS0:-91.5dBm
11ax HE40 MCS11:-62dBm
11ax HE80 MCS0:-88dBm
11ax HE80 MCS11:-58dBm
11ax HE160 MCS0:-85.5dBm
11ax HE160 MCS11:-55dBm

Uradna stran proizvajalca: <https://www.tp-link.com/us/home-networking/wifi-router/archer-ax73/#overview>
